





Characteristics



- vandal-proof
- stainless steel wall hung urinal trough with integrated flushing head
- different lenghts could be made to order
- material AISI 304
- brushed finish

Dimensions

2400(SLPN 05) Water inlet Rate of flow 1200(SLPN 03) 600(SLPN 02) SLPN 03 SLPN 04 SLPN 05

Technical Specification

male thread G 1/2"

12 I/min. by the pressure 0,3 MPa (inf. data) 24 I/min. by the pressure 0,3 MPa (inf. data) 36 I/min. by the pressure 0,3 MPa (inf. data) 48 I/min. by the pressure 0,3 MPa (inf. data)

* for the height of the front edge of the urinal 650 mm above the floor

Supply Specification

SLPN 03 -

SLPN 02 - Supply No. 91020 stainless steel urinal trough 600 mm with flushing head (1 pc.),

angle valve with a filter, mounting set, cover for siphon, siphon stainless steel urinal trough 1200 mm with flushing head (2 pcs.),

angle valve with a filter, mounting set, cover for siphon, siphon SLPN 04 - Supply No. 91040 stainless steel urinal trough 1800 mm with flushing head (3 pcs.)

N 04 - Supply No. 91040 stainless steel urinal trough 1800 mm with flushing head (3 pcs.), angle valve with a filter, mounting set, cover for siphon, siphon

SLPN 05 - Supply No. 91050 stainless steel urinal trough 2400 mm with flushing head (4 pcs.), angle valve with a filter, mounting set, cover for siphon, siphon

Recommended Accessories

Supply No. 91030

SLP 01Z - Supply No. 01011 time-controlled flushing unit for urinal troughs

SLP 05N - Supply No. 42052 automatic flushing unit for a group of urinals, 24 V DC

SLP 05NZ - Supply No. 42053 automatic flushing unit for a group of urinals and integrated power supply, 230 V AC