





Characteristics









- economical aerator, rate of fl ow 6 l/min
- hvaienic flush
- suitable for medical facilities
- SLVN 02 stainless steel floor standing cleaner's sink with washbasin and grating, without a tap hole (could be made to order), is destined for the installation to the open space
- SLVN 02E stainless steel floor standing combined cleaner's sink with washbasin, grating and automatic tap SLU 08LND (swivel faucet, START/STOP program)
- SLVN 02EB stainless steel floor standing combined cleaner's sink with washbasin, grating and automatic tap SLU 08LNDB (swivel faucet, START/STOP program)
- material stainless steel AISI 304 (1.4301)
- brushed finish

Dimensions



SLVN 02



SLVN 02E, EB

Technical Specification

Dimensions

■ SLVN 02	890 x 690 x 500 mm
■ SLVN 02E	1196 x 690 x 500 mm
■ SLVN 02EB	1196 x 690 x 500 mm

Weight

weight	
SLVN 02	18,6 kg
SLVN 02E	22,5 kg
SLVN 02EB	22,44 kg

Thickness of material

· · · · · · · · · · · · · · · · · · ·	
■ sink	1 mm
apron	0,8 mm
Operating voltage	
SLVN 02E	24 V DC

SLVN 02EB	6 V
Power input	
■ operating by 24 V	1.4 W

operating by 6 V **Battery life**

 4 pcs. AA alkaline batteries
AA, 1,5 V, 2700 mAh

Rate of flow Water inlet Water temperature regulation

approx. 2 years (100 uses per day) 12 l/min. (inf. data) male thread G 1/2" integrated mixer

11 W

Supply Specification

stainless steel cleaner's sink with washbasin, grating, siphon, SLU 08LND (SLVN 02E), SLVN 02 -**Supply No. 98020 SLVN 02E -Supply No. 98021** SLU 08LNDB and 4 pcs. AA alkaline batteries 1,5 V, 2700 mAh with battery case

SLVN 02EB - Supply No. 98022 (SLVN 02EB)

Stainless Steel Cleaner's Sinks

Recommended Accessories

SLZ 01Y	-	Supply No. 05012	power supply 24 V DC for operating of max. 10 pcs. washbasin taps
SLZ 01Z	-	Supply No. 05011	power supply 24 V DC for operating of max. 20 pcs. washbasin taps
SLZ 04Y	-	Supply No. 05042	power supply 24 V DC for DIN rail, for operating of max. 10 pcs. washbasin taps
SLZ 04Z	-	Supply No. 05041	power supply 24 V DC for DIN rail, for operating of max. 20 pcs. washbasin taps
SLZ 04X	-	Supply No. 10049	power supply 24 V DC for DIN rail, for operating of max. 30 pcs. washbasin taps
SLZ 06	-	Supply No. 05060	power supply 24 V DC for operating of max. 1 pc. of washbasin tap
SLD 03	-	Supply No. 07030	remote control for an adjustment of parameters
SI A 36 .	_	Supply No. 06360	set of 4 ncs, alkaline batteries AA 1.5 V 2700 mAb (for models with index B)